

HUB-RETTUNGSGERÄT MARK ROBIN HUB

HUB-RESCUE DEVICE MARK ROBIN HUB

BESCHREIBUNG

- Automatisch wirkendes Hub-Rettungsgerät mit dem Personen abgesiebt bzw. angehoben werden können. Durch 2 Fliehkraftbremsen wird der Abseilvorgang automatisch auf <2 m/s reguliert. Mit dem Handrad ist auch ein Anheben von bis zu 225 kg (2 Personen) möglich. Zusätzlich kann das Gerät mit Akkuschrauber bedient werden, um das Anheben zu erleichtern.

EINSATZGEBIETE

- Feuerwehr, Höhenrettung, Industrie, Seilbahnen, Hochregallager, Hochregalbediengeräte, ...

AUSSTATTUNG

- Gehäuse: Stahl- Aluminium Kombination
- Bremssystem: Automatisches, redundantes Bremssystem (2 Fliehkraftbremsen, Bremstrommeln aus Stahl)
- Karabiner: Automatische, AHK Aluminiumkarabiner
- Seil: Ø9,6 mm (86215) statisches Polyamid-Kernmantelseil nach EN 1891-A, wird in der gewünschten Länge am Gerät montiert.

TECHNISCHE DATEN

- Norm: EN 341:2011-1A (2 Personen), EN 1496:2017 B (2 Personen), ANSI Z359.4 (1 Person), EN 12841 (1 Person)
- Max. Last: 225 kg
- Max. Abseihöhe: 500 m
- Abseilgeschwindigkeit: <2 m/s
- Prüfintervall: Regelmäßige Überprüfung je nach Verwendung (siehe Gebrauchsanleitung) jedoch spätestens alle 12 Monate

DESCRIPTION

- Automatic acting rescue device for descending or lifting persons. The descending is automatically regulated to <2 m/sec. by 2 centrifugal brakes. The handwheel can also be used to lift up to 225 kg (2 persons). In addition, the device can be operated with cordless screwdriver to make lifting easier

RANGES OF APPLICATION

- Fire brigade, height rescue, industry, ropeway, high bay storage, ...

EQUIPMENT

- Housing: Steel-aluminium combination
- Brake system: Automatic, redundant brake system (2 centrifugal brakes, steel brake drums)
- Carabiner: Automatic, AHK aluminium carabiner
- Rope: Ø9,6 mm (86215) static polyamide kernmantle rope according to EN 1891-A, is mounted to the device in the desired length.

TECHNICAL DATA

- Standard: EN 341:2011-1A (2 persons), EN 1496:2017 B (2 persons), ANSI Z359.4 (1 person), EN 12841 (1 person)
- Max. load: 225 kg
- Max. descend height: 500 m
- Descend speed: <2 m/s
- Inspection Interval: Regular checks depending on use (see instruction of use), but at least every 12 months



PRODUKT / PRODUCT

Hub-Rettungsgerät MARK Robin Hub

BEST. NR. / ART. NO.

4215310

MARK Kernmantelseil

Ø 9,6 mm

4240009

Statisches Polyamid-Kernmantelseil wird in der gewünschten Länge am Gerät montiert.
Static polyamide kernmantle rope is mounted to the device in the desired length

RETTUNGSKLEMME RESCUE CLAMP

BESCHREIBUNG

- Universell einsetzbare Seilklemme für Seile, Bandmaterial und Stahlseile.

TECHNISCHE DATEN

- Norm: EN 567:2013
- Seil: Ø8-16 mm
- Bandmaterial: 20-30 mm und ≥1,5 mm
- Stahlseil: 4-5 mm

DESCRIPTION

- Universal rope clamp for Ropes, webbing and wire cables.

TECHNICAL DATA

- Standard: EN 567:2013
- Rope: Ø8-16 mm
- Webbing: 20-30 mm and ≥1,5 mm
- Wire cable: 4-5 mm

PRODUKT / PRODUCT

Rettungsklemme

BEST. NR. / ART. NO.

4290094

