

NACH NORMENSTANDARD: EN 694
ACCORDING TO: EN 694



PRODUKT / PRODUCT

BEST. NR. / ART. NO.


Innendurchmesser inner diameter		max. Arbeitsdruck max. work pressure		Prüfdruck** test pressure		Platzdruck burst pressure		Gewicht weight		Biegeradius bending radius	Länge length	ohne Kupplung no couplings
mm	inch	bar	p.s.i.	bar	p.s.i.	bar	p.s.i.	kg/m	lb/feet	mm		
19 weiß white	3/4	30	435	50	725	80	1160	0,12	0,08	90	15 m	362334
											20 m	365092
											30 m	362347
											60 m	365015
25 weiß white	1	30	435	50	725	80	1160	0,15	0,10	100	15 m	360106
											20 m	360107
											30 m	365286
											60 m	377816
27 weiß white	1	30	435	50	725	80	1160	0,16	0,11	100	15 m	360100
											20 m	365212
											30 m	360103
											60 m	360105

Weitere Dimensionen auf Anfrage / other dimensions on request
** laut Norm / according to the norm

STABILO-STAR YELLOW

SIEHE SEITE 21
REFER TO PAGE 21

NACH NORMENSTANDARD: EN 694
ACCORDING TO: EN 694



PRODUKT / PRODUCT

BEST. NR. / ART. NO.

Innendurchmesser inner diameter		max. Arbeitsdruck max. work pressure		Prüfdruck** test pressure		Platzdruck burst pressure		Gewicht weight		Biegeradius bending radius	Länge length	ohne Kupplung no couplings
mm	inch	bar	p.s.i.	bar	p.s.i.	bar	p.s.i.	kg/m	lb/feet	mm		
19*	3/4	30	435	50	725	80	1160	0,14	0,09	100	25 m	300278
											30 m	300273
											60 m	377316
25*	1	30	435	50	725	80	1160	0,17	0,11	120	25 m	300269
											30 m	300267
											60 m	300307

Weitere Dimensionen auf Anfrage / other dimensions on request
** laut Norm / according to the norm